



Telecommunication Energy Storage Lithium Battery 48V 200AH Matt Black Shell

Our Product Introduction

for more products please visit us on rechargeable-liionbattery.com

Basic Information

- Place of Origin: Changsha, China
- Brand Name: HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Model Number: HY00035
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms: L/C, T/T
- Supply Ability: 10,000 PCS per month



Product Specification

- Name: Energy Storage Lithium Battery
- Model: 48V/8.8KWh/3KW
- L X W X H: 800mmx435mmx732mm
- Working Temperature: -20°C ~ 60°C
- Working Current: 75A
- Applications: 145KG
- Highlight: lithium ion storage battery,
solar rechargeable lithium batteries

Product Description

Telecommunication Energy Storage Lithium Battery 48V 200AH Matt Black Shell

Model: 48V/8.8KWh/3KW

Specification L x W x H: 800mmx435mmx732mm

Features: Inverter integrated 48vdc-220vac-3kw, dual CPU intelligent control technology, mains mode / energy saving mode / battery mode can be set, charging current 30A (default) - C0-C6 can be set, battery type U0-U7 can be set, Pure sine wave AC output, LCD display device automatic protection and alarm prompt, continuous working current 75A, instantaneous maximum current 150A, weight 145KG

Applications :

Solar and wind energy storage system

EPS and UPS battery backup

Signal system , emergency lighting system , security system

Telecommunication Equipment

Power plant and transmission system

			Number	HY00035
			Version	A0
	HYLF/48V/9.6KWH-001		Date	2019-5-8
Battery pack specification				
1 Basic characteristics				Product picture
Product name	Lithium battery pack			
product code	HYLF/48V/9.6KWH-001			
L x W x H	800mmmX435mmx732mm			
Rated voltage				
Rated Capacity	200AH			
Serialization	2P15SAluminum shell			
Internal resistance	≤120mΩ			
Discharge cutoff voltage	34.5V			
Charging protection voltage	54V			
Max.charging voltage	54.75V			
Max. charging current	30A			
Max. sustained discharge current	75A			
Peak current	150±3A 2S			
Rated discharge current	75A			3000KWBuilt-in 3000KW inverter integrated machine
				Shell color
				☒ Matt black
				☐ Bright gray
		☐ Fruit green + bright gray (two colors)		
		☐ White		
		Charging and discharging interface		
		☐ Wall terminal		
		☐ Anderson		
		☐ Air plug		
		☐ Positive and negative lines		
		☒ Terminal post		
		LEDThe power box has a universal wheel with a positioning pin, a handle, and an LED function display.		
		48vdc-220vac-3kw,CPUInverter integrated machine 48vdc-220vac-3kw, dual CPU intelligent control technology		
		30A-C0-C6,U0-U7,Mains mode / energy saving mode / battery mode can be set, charging current 30A default - C0-C6 can be set, battery type U0-U7 can be set, pure sine wave AC output		
		Batteries:3.2v/100Ah		
Charging method	CC/CV			
weight	155Kg			
Operating temperature	Charging	0 45		
	Discharge	-20 45		
60-80%SOC , 2 Storage temperature	-10 35			
60-80% SOC storage, need to recharge every 2 months				
C1 Cycle life	1500 Times			
price	RMB:¥ 00.00			
		Cell discharge performance		

Delivery period	25 Working day	
-----------------	----------------	--



Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.