



High Density Special Lithium Battery 24V 40000mAh Fast Charge Capability

Basic Information

Place of Origin: Changsha, China

• Brand Name: HYZZ

• Certification: ISO9001, CE, CB, UN38.3

Packaging Details: foam, wooden box / foam, carton, tray

Delivery Time: 22 daysPayment Terms: L/C, T/T

Supply Ability: 10,000 PCS per month



Product Specification

• Name: Special Lithium Battery

• Model: 24V 40000mAh

• L X W X H: 440mmX220mmX130mm

• Working Temperature: Under -40°C Working Environment

Working Current: 3ADischarge Cut-off Voltage: 17.5V

• Highlight: large capacity lithium battery,

lithium ion phosphate battery

Product Description

High Density Special Lithium Battery 24V 40000mAh Fast Charge Capability

Model: 24V 40000mAh

Specification: 374mmX148mmx80mm

Features: effective discharge rate ≥75% under working environment of -40°C, cylindrical 18650 low temperature lithium battery, with bracket, charge cut-off voltage 29.4V, discharge cut-off voltage 17.5V, working current 3A, maximum working current 7.5A

Applications: Measuring instruments, meteorological instruments, polar surveys

Battery OEM Service:

- Selected color of shrinkable tube.
- Selected Discharge plug and Balance connector
- High quality OEM label are welcomed

Advantages:

- 1, High energy density
- 2, Factory price& High quality
- 4, Pollution-free
- 6, Good consistency, low self discharge
- 2, High working voltage for single battery cells
- 5, Safe and reliable, With short-circuit protection function,

Battery Warranty:

The period of warranty is one year from the date of shipment.

We guarantee to give a replacement in case of cells with defects proven due to manufacturing process instead of the customer abuse and misuse.

Our services:

- 1. Your enquiry will be replied in 8 working hours.
- 2. Professional engineers & Exclusive and unique battery solution
- 3. Good sales: From begining to end, any quality problem with our products, new free one will be replaced.
- 4. Good quality assurance: All the cells are A grade cells, 100% quality check and full one year warranty.

		Number	HY00050
		Version	A0
	HYLF/24/40-001	_	0040 5 7
	Battery pack specification	Date	2019-5-7
1 Basic characteristics		Product picture	
Product name	Low temperature lithium		
- roduot riumo	battery	_	
product code	HYLF/24/40-001	Working characteristics:-40 4,0.2C,75%.	
LxWxH	374mmX148mmx80mm	It was left at -40 ° C for 4 hours, discharged at 0.2	
Rated voltage	25.9VSeries structure	C, and the effective discharge rate was not lower	
Rated Capacity	40Ah	than 70% of the normal temperature capacity.	
Serialization	7S	1	
Internal resistance	≤100mΩ	1	
Discharge cutoff voltage	17.5V		
Charging protection voltage	29.4V	1	
Max.charging voltage	29.75V	1	
Max. charging current	8A		
Maximum discharge	7.5A	1	
current			
Peak current	15±3A 2S		
		Shell col	or
		□ Sub bla	ack
		□ Bright	gray
		-+Fruit	green + bright gray two-color
		□ White	
		☑ Blue th	nermoplastic film
		Charging	g and discharging interface erminal

			_	
			□ Anderson	
			□ Navigation plug	
			☑ Positive and negative lines	
	1		□ Pole □ Hardware contact	
Rated discharge current	3.5A			
Charging method	CC/CV			
weight	6.65kg			
Operating temperature	Charging 0 45			
	Discharge	-40 55		
60-80%SOC , 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35			
C1 Cycle life Cycle life	500 Times]	
price	RMB:¥ 00.00		1	
Delivery period	25 Working day		1	



Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.