



## 24V 200AH Industrial Lithium Batteries Lithium Iron Phosphate Marine Battery

Our Product Introduction

for more products please visit us on [rechargeable-liionbattery.com](http://rechargeable-liionbattery.com)

### Basic Information

- Place of Origin: Changsha, China
- Brand Name: HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms: L/C, T/T
- Supply Ability: 10,000 PCS per month



### Product Specification

- Name: Industrial Lithium Batteries
- Model: 24V 200AH
- L X W X H: 545mm\*245mm\*190mm
- Working Environment: -20°C-60°C
- Charge Cut-off Voltage: 29.2V
- Working Current: 150A
- Highlight: **industrial lithium ion battery,**  
**industrial rechargeable battery**

## Product Description

### 24V 200AH Industrial Lithium Batteries Lithium Iron Phosphate Marine Battery

Model: 24V 200AH

Specification: 545mm\*245mm\*190mm

Parameters: -20°C-60°C working environment, lithium iron phosphate, charge cut-off voltage 29.2V, discharge cut-off voltage 20V, working current 150A, maximum working current 200A, charging 100A, sheet metal box, black

Applications: Measuring instruments, meteorological instruments, power grids, engineering equipment

- \* No maintenance
- \* High safety and reliability
- \* Longer life
- \* Low self discharge rate
- \* Great conductivity
- \* Great adaptability to environment
- \* Great directionality
- \* Environment friendliness

		Number	HY00063		
		Version	A0		
	<b>HYLF/24/200-001</b> Battery pack specification	Date	2019-5-7		
<b>1 Basic characteristics</b>		Product picture			
Product name	Industrial lithium battery	Batteries:-3.2V100AH Battery: lithium iron phosphate aluminum shell -3.2V100AH			
product code	HYLF/24/200-001				
L x W x H	545mm*245mm*190mm				
Rated voltage	25.6V Series structure				
Rated Capacity	100Ah				
Serialization	2P8S				
Internal resistance	≤100mΩ				
Discharge cutoff voltage	18.4V	Shell color			
Charging protection voltage	28.8V	<input checked="" type="checkbox"/> Sub black			
Max.charging voltage	29.2V	<input type="checkbox"/> Bright gray			
Max. charging current	100A	<input type="checkbox"/> +Fruit green + bright gray two-color			
Maximum discharge current	180A	<input type="checkbox"/> White			
Peak current	300±2A 2S	<input type="checkbox"/> Blue thermoplastic film			
Rated discharge current	150A	Charging and discharging interface			
		<input type="checkbox"/> Wall terminal			
		<input checked="" type="checkbox"/> Anderson			
		<input type="checkbox"/> Navigation plug			
		<input type="checkbox"/> Positive and negative lines			
		<input type="checkbox"/> Pole			
		<input type="checkbox"/> Hardware contact			
Charging method	CC/CV	Batteries:3.2v/100Ah  Cell discharge performance			
weight	44Kg				
Operating temperature	Charging			0 45	
	Discharge			-20 55	
60-80%SOC , 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35				
C1 Cycle life Cycle life	1500 Times				
price	RMB:¥ 00.00				
Delivery period	25 Working day				



## Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.