



# High Capacity Rechargeable Batteries 24V 10AH , Industrial Deep Cycle Battery

# **Basic Information**

- Place of Origin:
- Changsha, China
- Brand Name:
- HYZZ ISO9001, CE, CB, UN38.3
- Certification: ISO9001, CE, CB, UN38.3
  Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms:
- Supply Ability:
- L/C, T/T
- 10,000 PCS per month

24V/10AH

-20°C-60°C

29.2V



# Our Product Introduction

- Product Specification
- Name:
- Model:

Current:Highlight:

- L X W X H:
- Working Environment:
- Charge Cut-off Voltage:
- Continuous Working 5A
  - industrial rechargeable battery, industrial grade battery

Industrial Lithium Batteries

182mm\*78mm\*176mm

## **Product Description**

### High Capacity Rechargeable Batteries 24V 10AH , Industrial Deep Cycle Battery

### Model: 24V/10AH

Specification: 182mm\*78mm\*176mm

Parameters: working temperature -20°C-60°C, lithium iron phosphate battery, continuous working current 5A, 4A charging, instantaneous maximum current 30A (2S), Anderson interface, charging upper limit 29.2V, discharge cut-off 19.2V, stainless steel housing, two groups Series 96V use, weight 48KG.

### Application

- \* UPS System
- \* Security System
- \* Telecommunication Equipment
- \* Electric Tools and Electric Toys \* Portable Television and Video Equipment
- \* Portable Measuring and Medical Electronic Instruments
- \* Lighting System, Emergency \* Power station and telecom station

### Features

Full automatic transition of CC, CV and Float/cut-off Precise limit of voltage & current, guanrantee fully charged and voild over charge

Protections: Over current, over voltage, short circuit and reverse polarity

Current & voltage display, two LED indicators, aluminium, robust, elegant and hard, endurable

CE & C-Tick Certificate, safety, high quality

Patent Pending, 2-year Warranty

PFC

			Number	HY00064
			Version	A0
	HYLF/24/1		Date	2019-5-7
		< specification		
1 Basic characteristics		Product	picture	
Product name	182mm*78mm*176mm		Batteries:-3.2V5AHBattery: lithium iron phosphate	
product code				
L×W×H				
Rated voltage	25.6VSeries structure			
Rated Capacity	10Ah		Shell material: stainless steel	
Serialization	2P8S			
Internal resistance	≤100mΩ			
Discharge cutoff voltage	19.2V	19.2V Shell color		or
Charging protection voltage	28.8V		□ Sub black	
Max.charging voltage	29.2V		□ Bright gray	
Max. charging current	4A		-	
Maximum discharge	1			
current	30A		–□ White	
Peak current	50±2A 2S			
Rated discharge current	5A		<ul> <li>Wall te</li> <li>Anders</li> <li>Naviga</li> <li>Positiv</li> <li>Pole</li> </ul>	
Charging method	CC/CV		-	
weight	2.8Kg			
	Charging	0 45		
Operating temperature	Discharge	-20 55		

Our Product Introduction

60-80%SOC, 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35		
C1 Cycle life Cycle life	1500 Times		
price	RMB:¥ 00.00		
Delivery period	25 Working day		
	15616151876	info@pinshengenergy.com e rechargeable-liionbattery.com	

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.