



High Current Lithium Battery 60V 30AH , Portable Industrial Forklift Batteries

Our Product Introduction

Basic Information

- Place of Origin: Changsha, China
- Brand Name: HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms: L/C, T/T
- Supply Ability: 10,000 PCS per month



Product Specification

- Name: Industrial Lithium Batteries
- Model: 60V/30AH
- L X W X H: 365mm*190mm*180mm
- Working Environment: -20°C-60°C
- Weight: 17.6KG
- Continuous Working Current: 50A
- Highlight: industrial rechargeable battery,
industrial grade battery

for more products please visit us on rechargeable-liionbattery.com

Product Description

High Current Lithium Battery 60V 30AH , Portable Industrial Forklift Batteries

Model: 60V/30AH

Specification: 365mm*190mm*180mm

Parameters: working temperature -20°C-60°C, lithium iron phosphate battery 19S, continuous working current 50A, 6A charging, instantaneous maximum current 80A (2S), AWG8#-350mm, with OT10-6 terminal, charging upper limit 69.35V, discharge The cut-off of 44.65V, cold-rolled sheet spray, weight 17.6KG.

Applications: Measuring instruments, meteorological instruments, power grids, engineering equipment

Features

1. High temperature resistance
2. High working voltage for single battery cells
3. Pollution-free
4. Long cycle life(≥1800 times)
5. No memory effect
7. With short-circuit protection function, safe and reliable
8. Factory price& High quality
9. No self discharge
10. Light weight, small size

		Number	HY00068	
		Version	A0	
	HYLF/60/30-001 Battery pack specification	Date	2019-5-7	
1 Basic characteristics		Product picture		
Product name	Industrial lithium battery		Batteries:Lithium iron phosphate battery	
product code	HYLF/60/30-001			
L x W x H	365mm*190mm*180mm			
Rated voltage	60VSeries structure			
Rated Capacity	30Ah		Shell material: epoxy resin board packaging, optional sheet metal, plastic shell, aluminum alloy, etc.	
Serialization	19S			
Internal resistance	≤100mΩ			
Discharge cutoff voltage	44.65V			
Charging protection voltage	68.4V		<div><input checked="" type="checkbox"/> Sub black</div> <div><input type="checkbox"/> Bright gray</div> <div><input type="checkbox"/> +Fruit green + bright gray two-color</div> <div><input type="checkbox"/> White</div> <div><input type="checkbox"/> Blue thermoplastic film</div> <div>Charging and discharging interface</div> <div><input type="checkbox"/> Wall terminal</div> <div><input type="checkbox"/> Anderson</div> <div><input type="checkbox"/> Navigation plug</div> <div><input checked="" type="checkbox"/> Positive and negative lines</div> <div><input type="checkbox"/> Pole</div> <div><input type="checkbox"/> Hardware contact</div>	
Max.charging voltage	69.35V			
Max. charging current	6A			
Maximum discharge current	50A			
Peak current	80±5A 2S			
Rated discharge current	30A			
Charging method	CC/CV			
weight	17.6Kg			
	Charging	0 45		
Operating temperature	Discharge	-20 55		
60-80%SOC , 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35			
C1 Cycle life	1500 Times			
Cycle life				

price	RMB:¥ 00.00
Delivery period	25 Working day



Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.