



High Performance Rechargeable Lithium Ion Battery Type 18650 Long Cycle Life

Our Product Introduction

for more products please visit us on rechargeable-liionbattery.com

Basic Information

- Place of Origin: Changsha, China
- Brand Name: HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms: L/C, T/T
- Supply Ability: 10,000 PCS per month



Product Specification

- Name: Rechargeable Li Ion Battery
- Model: 12V 30Ah
- L X W X H: 280mmX135mmx120mm
- Application: Emergency Backup Power Supply, Outdoor Backup Power Supply, Portable Power Supply
- DC Output: 12V
- Weight: 3.5KG
- Highlight: **18650 lithium rechargeable battery ,
18650 replaceable battery**

Product Description

High Performance Rechargeable Lithium Ion Battery Type 18650 Long Cycle Life

Model: 12V 30Ah

Dimension:280mmX135mmx120mm;

Feature:

Conversion time:5ms;Analog sine wave; AC input:AC110V~220V,DC input:DC18V-36V;Car input:12V,DC output:12V,USB 5V;Weight:3.5KG

Application:Emergency backup power supply, outdoor backup power supply, portable power supply

HIGH DISCHARGING CURRENT

HIGH QUALITY

COMPETITIVE PRICE

- ◇ Green product
- ◇ Long standby time
- ◇ One year warranty
- ◇ Excellent safety performance
- ◇ Excellent storage performance and low self-discharge rate
- ◇ Short circuit testing passed
- ◇ Overcharge testing passed
- ◇ Over discharge testing passed
- ◇ 150C thermal shock test passed
- ◇ 1.2m drop testing passed

		Number	HY.NO007
		Version	A0
	HYLF/12/30-001 Battery pack specification	Date	2019-5-7
1 Basic characteristics		Product picture	
Product name	Portable power supply		Battery: ternary lithium battery
product code	HYLF/12/30-001		
L x W x H	280mmX135mmx120mm		
Rated voltage	12VSeries structure		
Rated Capacity	30Ah		
Serialization	4S		
Internal resistance	≤100mΩ		
Discharge cutoff voltage	11.2V	Shell color	
Charging protection voltage	16.8V	☐ Sub black	
Max.charging voltage	17V	☐ Bright gray	
Max. charging current	10A	☐ +Fruit green + bright gray two-color	
Maximum discharge current	25A	☐ White+ black	
Peak current	50±5 2S		
Rated discharge current	15A	☐ Blue thermoplastic film	
		Charging and discharging interface	
		☐ Wall terminal	
		☐ Anderson	
		☐ Navigation plug	
		☐ Positive and negative lines	
		☐ Pole	
		☐ Hardware contact	
Charging method	CC/CV		5ms,,AC110V~220V,DC18V-36V,12V,12V,USB 5V.Features: conversion time 5ms, analog sine wave, AC input AC110V~220V, DC input DC18V-36V, car 12V input, DC output 12V, USB 5V.
weight	3.5Kg		
Operating temperature	Charging	0 45	
	Discharge	-20 55	
60-80%SOC , 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35		

C1 Cycle life	1500 Times
Cycle life	
price	RMB:¥ 00.00
Delivery period	25 Working day



Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.