



Rechargeable 18650 Lithium Ion Battery 24V 12Ah For Measuring Instruments

Basic Information

Place of Origin: Changsha, China

• Brand Name: HYZZ

• Certification: ISO9001, CE, CB, UN38.3

Model Number: HY00083

• Packaging Details: foam, wooden box / foam, carton, tray

Delivery Time: 22 daysPayment Terms: L/C, T/T

• Supply Ability: 10,000 PCS per month



Product Specification

Name: Rechargeable Li Ion Battery

• Model: 24V 12Ah

• L X W X H: 148mmX82mmx80mm

Application: Measuring Instruments, Meteorological

Instruments, Etc.

Charge Cut-off Voltage: 29.4V Weight: 1.9KG

• Highlight: 18650 lithium rechargeable battery,

18650 replaceable battery

Product Description

Rechargeable 18650 Lithium Ion Battery 24V 12Ah For Measuring Instruments

Model: 24V 12Ah

Dimension:148mmX82mmx80mm;

Feature:

Cylinder 18650/7S3P; Charge cut-off voltage:29.4V, discharge cut-off voltage:19.6V, operating current:12A, maximum 30A, DC terminal, weight:1.9KG.

Application Lithium battery:

Mobile phones, tablets, Bluetooth headsets, smart watches and other smart wearable devices, GPS, electric toys, beauty instruments, aromatherapy machines, LED lights, quadcopters, drones ,etc.

Application Lithium battery pack:

E-bike, power tools, new energy vehicles, medical equipment, digital cameras, measuring instruments, robots, etc.

Tips: If you see our products and have questions about the products, please contact our account manager to send your specific needs, such as voltage, capacity, shape, size, working current, etc. We can customize and meet your needs according to your needs. The best lithium battery matched by the equipment, we are very happy to provide you with test samples, and will reply you as soon as possible, thank you!

			Number	HY00083		
				A0		
	HYLF/24/1	2-001				
	ı	specification	Date	2019-5-7		
1 Basic characteristic		-	Product	picture		
Product name	Industrial lithium battery					
product code	HYLF/24/12	-001	7			
LxWxH	148mmX82ı	mmx80mm	Batteries	:Battery: Ternary lithium battery		
Rated voltage	24VSeries s	tructure	:,,DCBat	tery pack: battery indicator, output switch,		
Rated Capacity	12Ah		DC head			
Serialization	7S					
Internal resistance	≤100mΩ					
Discharge cutoff	19.6V		Shell color			
voltage						
Charging protection voltage	29.4V			□ Sub black		
Max.charging voltage	29.75V		□ Bright gray			
Max. charging current	4A		L Fruit	areen + bright gray two color		
Maximum discharge	25A		ー□ +Fruit green + bright gray two-color			
current			│ ─□ White+ black			
Peak current	40±2 2S		_			
Rated discharge current	12A		Charging Wall te Anders Naviga Positiv	· · · · · ·		
Charging method	CC/CV					
weight	1.9Kg		_			
		0 45	_			
Operating temperature	Discharge	-20 55				
60-80%SOC , 2 Storage temperature						
60-80% SOC storage, need to recharge every 2 months	-10 35					
60-80% SOC storage, need to recharge	-10 35 1500 Times RMB:¥ 00.0					

Delivery period	25 Working day	

Hunan Pinsheng Energy Technology Co., LTD.

● 15616151876 info@pinshengenergy.com erchargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.