



High Performance Lithium Solar Batteries 48 Volt 200AH For Solar Street Light

Our Product Introduction

Basic Information

- Place of Origin: Changsha, China
- Brand Name: HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms: L/C, T/T
- Supply Ability: 10,000 PCS per month



Product Specification

- Name: Rechargeable Li Ion Battery
- Model: 48V 200AH
- L X W X H: 510mm*380mm*170mm
- Application: Wall-mounted Household Energy Storage
- Charge Cutoff Voltage: 57.6V
- Working Environment: -20 -60
- Highlight: lithium ion solar battery, solar system batteries

for more products please visit us on rechargeable-liionbattery.com

Product Description

High Performance Lithium Solar Batteries 48 Volt 200AH For Solar Street Light

Model: 48V 200AH

Dimension: 510mm*380mm*170mm

Parameter:

working environment:-20 -60 ;battery: Lithium iron phosphate battery 16S;Charge cutoff voltage:57.6V;Discharge cutoff voltage:38.4V;
Continuous 100A discharge; 50A Charging;

Application:

LED strip/panel/light
Camera/IP Camera
Car camera recorder
Router/Switch
POS machine
Solar energy storage
Speaker and so on

Why you choose us ?

1. We can provide OEM service ,custom your logo both on the product and the packing you want !
2. High quality products ,all of the products must passed strict QC before shipping ,0.01% defective rate !
3. Fastest response rate ,save your time and easy your business !
4. Safe payment methods ,Safe business ,we support T/T,western union ,paypal,trade assurance
5. We provide after-sale service,all of our goods have 1-3 year warranty

		Number		HY00081					
		Version		A0					
		HYLF/48/200-001		Date		2019-5-7			
		Battery pack specification							
1 Basic characteristics				Product picture					
Product name		Wall-mounted household energy storage lithium battery		Batteries:3.2V100AHBattery: lithium iron phosphate battery 3.2V100AH					
product code		HYLF/48/200-001							
L x W x H		510mm*380mm*170mm							
Rated voltage		48VSeries structure							
Rated Capacity		200Ah							
Serialization		2P16S							
Internal resistance		≤100mΩ		Shell color <input type="checkbox"/> Sub black <input type="checkbox"/> Bright gray <input type="checkbox"/> +Fruit green + bright gray two-color <input checked="" type="checkbox"/> White+ black <input type="checkbox"/> Blue thermoplastic film Charging and discharging interface <input checked="" type="checkbox"/> Wall terminal <input type="checkbox"/> Anderson <input type="checkbox"/> Navigation plug <input type="checkbox"/> Positive and negative lines <input type="checkbox"/> Pole <input type="checkbox"/> Hardware contact					
Discharge cutoff voltage		38.4V							
Charging protection voltage		57.6V							
Max.charging voltage		58.4V							
Max. charging current		50A							
Maximum discharge current		100A							
Peak current		200±5 2S							
Rated discharge current		50A							
Charging method		CC/CV		HYLF/48/200-0018Product features:					
weight		88Kg							
Operating temperature		Charging						0 45	
		Discharge						-20 55	

60-80%SOC , 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35	HYLF/48/200-001 can be used up to 8 units in combination
C1 Cycle life Cycle life	1500 Times	
price	RMB:¥ 00.00	
Delivery period	25 Working day	



Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.