



Large Lithium Iron Phosphate Rechargeable Battery For Electric Motorcycle

Our Product Introduction

Basic Information

- Place of Origin: Changsha, China
- Brand Name: HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms: L/C, T/T
- Supply Ability: 10,000 PCS per month



Product Specification

- Name: High Power Lithium Ion Battery
- Model: 12V 200AH
- L X W X H: 210mm*190mm*180mm
- Working Temperature: -20°C ~ 60°C
- Peak Current: 150±5A 2S
- Shell Color: 1500 Times
- Highlight: lifepo4 rechargeable battery, lithium ion lifepo4

for more products please visit us on rechargeable-liionbattery.com

Product Description

Large Lithium Iron Phosphate Rechargeable Battery For Electric Motorcycle

Model: 12V 200AH

Dimension: 210mm*190mm*180mm

Parameter:

working environment:-20 -60 ;Lithium iron phosphate battery:2P4S

Charge cutoff voltage:14.4V;Discharge cutoff voltage:9.6V; working current:80A; charge current:40A; plastic shell

Application:

Electric vehicle

Golf cart

Electric motorcycle

Electric boat

Electric forklift

Telecommunication

Distributed Grid Energy Storage system

Mining equipment

Solar energy storage system

Marine

Backup power

Household energy storage system

		Number	HY00073
		Version	A0
		Date	2019-5-7
	HYLF/12/200-001		
	Battery pack specification		
1 Basic characteristics		Product picture	
Product name	Industrial lithium battery	Batteries:3.2V100AHLithium iron phosphate aluminum shell 3.2V100AH	
product code	HYLF/12/200-001		
L x W x H	521mm*238mm*218mm	Shell material: epoxy resin board packaging, optional sheet metal, plastic shell, aluminum alloy, etc.	
Rated voltage	48VSeries structure		
Rated Capacity	200Ah	.In the above figure, the battery case is a lead- acid plastic case.	
Serialization	2P4S		
Internal resistance	≤100mΩ	Shell color	
Discharge cutoff voltage	9.6V		
Charging protection voltage	14.4V	<input checked="" type="checkbox"/> Sub black	
Max.charging voltage	14.6V		
Max. charging current	40A	<input type="checkbox"/> Bright gray	
Maximum discharge current	80A		
Peak current	150±5A 2S	<input type="checkbox"/> +Fruit green + bright gray two-color	
		<input type="checkbox"/> White	
		<input type="checkbox"/> Blue thermoplastic film	
		Charging and discharging interface	
		<input type="checkbox"/> Wall terminal	
		<input type="checkbox"/> Anderson	
		<input type="checkbox"/> Navigation plug	
		<input type="checkbox"/> Positive and negative lines	
		<input checked="" type="checkbox"/> Pole	
		<input type="checkbox"/> Hardware contact	
Charging method	CC/CV		
weight	27.3Kg		
Operating temperature	Charging	0 45	
	Discharge	-20 55	
60-80%SOC , 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35		
C1 Cycle life Cycle life	1500 Times		

price	RMB:¥ 00.00
Delivery period	25 Working day



Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.