



Portable 18650 Rechargeable Lithium Lifepo4 Battery 24V 12Ah 1.9KG Weight

Our Product Introduction

for more products please visit us on rechargeable-liionbattery.com

Basic Information

- Place of Origin: Changsha, China
- Brand Name: HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms: L/C, T/T
- Supply Ability: 10,000 PCS per month



Product Specification

- Name: Rechargeable Li Ion Battery
- Model: 24V 12Ah
- L X W X H: 148mmX82mmx80mm
- Application: Measuring Instruments, Meteorological Instruments, Etc.
- Internal Resistance: $\leq 100\text{m}\Omega$
- Peak Current: $40\pm 2\text{ 2S}$
- Highlight: **18650 rechargeable li ion battery ,
18650 replaceable battery**

Product Description

Portable 18650 Rechargeable Lithium Lifepo4 Battery 24V 12Ah 1.9KG Weight

Model: 24V 12Ah

Dimension:148mmX82mmx80mm;

Feature:

Cylinder 18650/7S3P; Charge cut-off voltage:29.4V, discharge cut-off voltage :19.6V, operating current :12A, maximum 30A, DC terminal, weight:1.9KG.

Application: Measuring instruments, meteorological instruments, power grids, engineering equipment

		Number		HY00083
		Version		A0
	HYLF/24/12-001	Date	2019-5-7	
Battery pack specification				
1 Basic characteristics			Product picture	
Product name	Industrial lithium battery		Batteries:Battery: Ternary lithium battery :,DCBattery pack: battery indicator, output switch, DC head	
product code	HYLF/24/12-001			
L x W x H	148mmX82mmx80mm			
Rated voltage	24VSeries structure			
Rated Capacity	12Ah			
Serialization	7S			
Internal resistance	≤100mΩ			
Discharge cutoff voltage	19.6V		Shell color	
Charging protection voltage	29.4V		<input type="checkbox"/> Sub black	
Max.charging voltage	29.75V		<input type="checkbox"/> Bright gray	
Max. charging current	4A		<input type="checkbox"/> +Fruit green + bright gray two-color	
Maximum discharge current	25A		<input type="checkbox"/> White+ black	
Peak current	40±2 2S		<input checked="" type="checkbox"/> Blue thermoplastic film	
Rated discharge current	12A	Charging and discharging interface		
		<input type="checkbox"/> Wall terminal		
		<input type="checkbox"/> Anderson		
		<input type="checkbox"/> Navigation plug		
		<input checked="" type="checkbox"/> Positive and negative lines		
		<input type="checkbox"/> Pole		
		<input type="checkbox"/> Hardware contact		
Charging method	CC/CV			
weight	1.9Kg			
Operating temperature	Charging	0 45		
	Discharge	-20 55		
60-80%SOC , 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35			
C1 Cycle life Cycle life	1500 Times			
price	RMB:¥ 00.00			
Delivery period	25 Working day			

FAQ

1. Q: Can you accept OEM and ODM Service?

A: Yes, we supply OEM&ODM service as clients requirement.

2. Q: Can we get samples for test?

A: Yes, we offer sample.

3. Q: What's your payment term?

A: T/T, Moneygram,West Union, Paypal etc.

4. Q: What's your warranty for products?

A: Generally speaking, it's one year's warranty, for quality problems, we will send you a new one.

5. Q: How long will be the delivery?

A: Usually delivery in 5-10 days, but could be changed according to the quantity or other things.

6. Q: How do you control your product quality.

A: All batteries tested twice during the whole production.



Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.