



12 Volt 18650 Lithium Ion Rechargeable Battery , High Voltage Eco Ion Battery

Our Product Introduction

for more products please visit us on rechargeable-liionbattery.com

Basic Information

- Place of Origin: Changsha, China
- Brand Name: HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Model Number: HY.NO0008
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms: L/C, T/T
- Supply Ability: 10,000 PCS per month



Product Specification

- Name: Rechargeable Li Ion Battery
- Model: 12V 75Ah
- L X W X H: 260mmX160mmX158mm
- Application: Emergency Backup Power Supply, Outdoor Backup Power Supply, Portable Power Supply
- Rated Discharge Current: 15A
- Charging Protection Voltage: 16.8V
- Highlight: **18650 rechargeable li ion battery, 18650 replaceable battery**

Product Description

12 Volt 18650 Lithium Ion Rechargeable Battery , High Voltage Eco Ion Battery

Model: 12V75Ah

Dimension:260mmX160mmx158mm;

Feature:

Conversion time:5ms;Analog sine wave; AC input:AC110V~220V,DC input:DC18V-36V;Car input:12V,DC output:12V,USB: 5V;Weight:4.8KG

Application:Emergency backup power supply, outdoor backup power supply, portable power supply




How to choose a high quality lithium battery:

- 1, A grade battery cell, with full capacity for each battery cell;
- 2, BMS: water proof, anti static, over current protection, over voltage protection, with sealed case;
- 3, IP55 water proof case, plastic or steel case available by customer's requirement. MOQ: 1pieces.

In order to guarantee A grade battery cell:

- 1, High grade raw material;
- 2, 12hours & 3 cycles charging/discharging test.

		Number	HY.NO0008
		Version	A0
	HYLF/12/75-001	Date	2019-5-7
	Battery pack specification		
1 Basic characteristics		Product picture	
Product name	Portable power supply	Battery: ternary lithium battery	
product code	HYLF/12/75-001		
L x W x H	260mmX160mmx158mm		
Rated voltage	12VSeries structure		
Rated Capacity	75Ah		
Serialization	4S		
Internal resistance	≤100mΩ		
Discharge cutoff voltage	11.2V	Shell color	
Charging protection voltage	16.8V	<input type="checkbox"/> Sub black	
Max.charging voltage	17V	<input type="checkbox"/> Bright gray	
Max. charging current	10A	<input type="checkbox"/> +Fruit green + bright gray two-color	
Maximum discharge current	25A	<input type="checkbox"/> White+ black	
Peak current	50±5 2S	<input type="checkbox"/> Blue thermoplastic film	
Rated discharge current	15A	Charging and discharging interface	
		<input type="checkbox"/> Wall terminal	
		<input type="checkbox"/> Anderson	
		<input type="checkbox"/> Navigation plug	
		<input type="checkbox"/> Positive and negative lines	
Charging method	CC/CV	<input type="checkbox"/> Pole	
		<input type="checkbox"/> Hardware contact	
weight	4.8Kg	5ms,,AC110V~220V,DC18V-36V,12V,12V,USB 5V.Features: conversion time 5ms, analog sine wave, AC input AC110V~220V, DC input DC18V-36V, car 12V input, DC output 12V, USB 5V.	
Operating temperature	Charging	0 45	
	Discharge	-20 55	
60-80%SOC , 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35		
C1 Cycle life	1500 Times		
Cycle life			
price	RMB:¥ 00.00		
Delivery period	25 Working day		

 15616151876  info@pinshengenergy.com  rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.