



Photovoltaic Energy Storage Lithium Battery 12Volt 200Ah Environmental Friendly

Basic Information

- Place of Origin:
- Changsha, China
- Brand Name:
- HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Packaging Details: foam, wooden box / foam, carton,
- Delivery Time:
- Payment Terms:
- Supply Ability:
- foam, wooden box / foam, carton, tray
- e: 22 days ms: L/C, T/T
- y: 10,000 PCS per month



Product Specification

- Name:
- Model:
- LXWXH:
- Working Temperature:
- Internal Resistance:
- C1 Cycle Life:
- Highlight:

- Energy Storage Lithium Battery
- 12V 200Ah
- 521mmX238mmx218mm
- -20°C ~ 60°C
- ≤120mΩ
- 1500 Times
- lithium ion storage battery , high capacity storage batteries

for more products please visit us on rechargeable-liionbattery.com

Product Description

Photovoltaic Energy Storage Lithium Battery 12Volt 200Ah Environmental Friendly

Model: 12V200Ah

Specifications L x W x H: 521mmX238mmx218mm

Features: Operating temperature -20° C ~ 60° C, lithium iron phosphate, charge cut-off voltage 14.4V, discharge cut-off voltage 10V working current 50A (adjustable), cycle life 1500 times, plastic case (the shell has four colors and 50 different Specifications are available for users to choose from)

Applications: Solar street light batteries, photovoltaic energy storage, mechanical equipment, lighting, etc.

			Number	HY00031	
			Version	A0	
	HYLF/12/2	200-001		0040.5.0	
	Battery pack	<pre>specification</pre>	Date	2019-5-8	
1 Basic characteristics		Product picture			
Product name Lithium battery pack					
product code	HYLF/12/200-001				
L x W x H	521mmX238mmx218mm			0	
Rated voltage	12.8V				
Rated Capacity	200AH				
Serialization	2P4SAluminum shell				
Internal resistance	≤120mΩ plastic shell		plastic sl	hell	
Discharge cutoff voltage	10.0V		Shell col	or	
Charging protection voltage	14.4V		 Matt black Bright gray Fruit green + bright gray (two colors) Stainless steel Charging and discharging interface 		
Max.charging voltage	14.6V				
Max. charging current	40A				
Max. sustained discharge current	50A				
Peak current	100±3A 2S				
ated discharge 50A urrent		Wall terminal Anderson Air plug Positive and negative lines Terminal post Batteries:3.2v/100Ah			
			Datienes.3.20/100An		
Charging method	CC/CV 31Kg				
weight					
	Charging 0 45				
Operating temperature	Discharge	-20 45			
60-80%SOC, 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35		Cell disc	Cell discharge performance	
C1 Cycle life	1500 Times		_		
price	RMB:¥ 00.00				
Delivery period	25 Working	day			

FAQ

Q Are you manufacturer or simply trading company?

A We are manufacturer, and we sincerely welcome you to visit our factory!

Q May I get the Free sample ?

A Yes, Pls Contacts Us To Get Free Sample!

Q Can I get a lower price if I order large quantities?

A Yes, cheaper prices with more bigger size orders.

Q Do you offer charger for battery?

A Yes, we do. If you also need charger, please mention it when sending inquiry.

Q How about your company intelligence?

A ISO9001 certification, China Hi-tech company, 10 million battery assurance, 8 patents, Almost all products are MSDS, UN38.3, IEC62133, CB,etc certificated.

Q How about the quality guarantee period?

for more products please visit us on rechargeable-liionbattery.com

(15616151876	info@pinshengenergy.com erchargeable	-liionbattery.com				
NO. 259, Lixiang East	Road, Xiangfeng Technology Industry Park, Changsha Cit	y, Hunan, China.				