



# 12V 150Ah High Power Lithium Ion Battery For Large Scale Energy Storage

#### **Basic Information**

Place of Origin: Changsha, China

• Brand Name: HYZZ

• Certification: ISO9001, CE, CB, UN38.3

Model Number: HY00032

• Packaging Details: foam, wooden box / foam, carton, tray

Delivery Time: 22 daysPayment Terms: L/C, T/T

• Supply Ability: 10,000 PCS per month



### **Product Specification**

Name: Energy Storage Lithium Battery

• Model: 12V150Ah

• L X W X H: 181mmX170mmx80mm

C1 Cycle Life: 1500 TimesPeak Current: 80±3A 2S

Applications: Photovoltaic Energy Storage, Mechanical

Equipment, Etc.

• Highlight: lithium ion storage battery,

solar rechargeable lithium batteries

#### **Product Description**

#### 12V 150Ah High Power Lithium Ion Battery For Large Scale Energy Storage

Model: 12V150Ah

Specifications L x W x H: 181mmX170mmx80mm

Features: working temperature -20°C ~ 60°C, lithium iron phosphate, charge cut-off voltage 14.6V, discharge cut-off voltage 10V working current

50A, cycle life 1500 times

Applications: Solar street light batteries, photovoltaic energy storage, mechanical equipment, lighting, etc.

			Number	HY00032	
			Version A0		
	HYLF/12/1	00-001	+	1	
	Battery pack specification		Date	2019-5-8	
1 Basic characteristics		Product picture			
Product name	Lithium battery pack			TO THE RESERVE OF THE PERSON O	
product code	HYLF/12/10	0-001	Barrier .		
LxWxH	260mmX18	5mmx148mm			
Rated voltage	12.8V				
Rated Capacity	100AH				
Serialization	4SAluminum shell				
Internal resistance	≤120mΩ		The picture above shows the sheet metal casing or the plastic casing.		
Discharge cutoff	10.0V				
voltage			Shell color		
Charging protection	14.4V		□ Matt black □ Bright gray □ Fruit green + bright gray (two colors) □ White □ Charging and discharging interface		
voltage	14.6V				
Max.charging voltage					
Max. charging current	50A				
Max. sustained discharge current	50A				
Peak current	80±3A 2S				
				□ Wall terminal □ Anderson □ Air plug	
			<ul> <li>☑ Positive and negative lines</li> <li>☑ Terminal post</li> </ul>		
Rated discharge 15A					
current	134			· '	
			Batterie	s:3.2v/100Ah	
Charging method	CC/CV				
weight	15Kg				
Operating temperature	Charging 0 45		_	_	
	Discharge	-20 45			
60-80%SOC , 2			Cell dis	charge performance	
Storage temperature	-10 35				
60-80% SOC storage,					
need to recharge					
every 2 months			_		
C1 Cycle life	1500 Times				
price	RMB:¥ 00.00				
Delivery period	25 Working	day			



## **Hunan Pinsheng Energy Technology Co., LTD.**



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com