




Deep Cycle Life Solar Rechargeable Lithium Batteries Residential Solar Battery

Basic Information

- Place of Origin:
- Changsha, China
- Brand Name:
- HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time:Payment Terms:
- Payment remis.
- Supply Ability:



10,000 PCS per month



Product Specification

- Name:
- Rated Capacity:
 - pacity: 200Ah H: 510mm*380mm*170mm
- L X W X H:Application:
- Rated Voltage:
- Working Environment: -
- Highlight:

48V -20 -60 lithium ion solar battery,

Wall-mounted Household Energy Storage

lithium solar replacement batteries

Lithium Solar Batteries

Product Description

Deep Cycle Life Solar Rechargeable Lithium Batteries Residential Solar Battery

Model: 48V 200AH

Dimension: 510mm*380mm*170mm

Parameter:

working environment:-20 -60 ;battery: Lithium iron phosphate battery 16S;Charge cutoff voltage:57.6V;Discharge cutoff voltage:38.4V; Continuous 100A discharge; 50A Charging;

Application:

LED strip/panel/light Camera/IP Camera Car camera recorder Router/Switch POS machine Solar energy storage Speaker and so on

Why you choose us ?

- 1. We can provide OEM service ,custom your logo both on the product and the packing you want !
- 2. High quality products ,all of the products must passed strict QC before shipping ,0.01% defective rate !
- 3. Fastest response rate ,save your time and easy your business !
- 4. Safe payment methods ,Safe business ,we support T/T,western union ,paypal,trade assurance
- 5. We provide after-sale service, all of our goods have 1-3 year warranty

			Number	Number HY00081		
			Version A0			
	HYLF/48/20	00-001	D	0010 5 7		
	Battery pack specification		Date	2019-5-7		
1 Basic characteristics		Product picture				
	Wall-mounted household					
	energy storage lithium battery		Batteries:3.2V100AHBattery: lithium iron phosphate battery 3.2V100AH			
product code	HYLF/48/200-001					
LxWxH	510mm*380mm*170mm					
Rated voltage	48VSeries structure					
Rated Capacity	200Ah					
Serialization	2P16S					
Internal resistance	≤100mΩ					
Discharge cutoff voltage	38.4V		Shell color			
Charging protection voltage	57.6V		□ Sub black			
Max.charging voltage	58.4V	58.4V		🗆 Bright gray		
Max. charging current	50A		1			
Maximum discharge current	100A		+Fruit green + bright gray two-color			
Peak current	200±5 2S		- White+ black			
Rated discharge 50A current			Charging Wall te Anders Naviga Positiv Pole			
Charging method	CC/CV					
weight	88Kg		:HYLF/48/200-0018Product features:			
Operating temperature	Charging 0 45		HYLF/48/200-001 can be used up to 8 units in combination			
	Discharge 20 55					
1	1		1			

Cycle life	60-80%SOC, 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35
	C1 Cycle life Cycle life	1500 Times
Delivery period 25 Working day	price	RMB:¥ 00.00
	Delivery period	25 Working day

G	15616151876	info@pinshengenergy.com	e rechargeable-liionbattery.com				
NO.	259, Lixiang East	Road, Xiangfeng Technology Industry	y Park, Changsha City, Hunan, China.				