



Custom Lithium Polymer Battery 48 Volt 36Ah Lightweight For Balance Car

Our Product Introduction

for more products please visit us on rechargeable-liionbattery.com

Basic Information

- Place of Origin: Changsha, China
- Brand Name: HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms: L/C, T/T
- Supply Ability: 10,000 PCS per month



Product Specification

- Name: Rechargeable Li Ion Battery
- Model: 48V 36Ah
- L X W X H: 280mmX160mmx124mm
- Application: Balance Car
- Discharge Cutoff Voltage: 39.2V
- Charging Protection Voltage: 58.8V
- Highlight: **li polymer battery,
rechargeable lithium polymer battery**

Product Description

Custom Lithium Polymer Battery 48 Volt 36Ah Lightweight For Balance Car

Model: 48V 36Ah

Dimension: 280mmX160mmx124mm

Features:

ternary soft pack lithium battery, 14S; charge cut-off voltage :58.8V; discharge cut-off voltage :39.2V; rated current :30A ; electric large working current :50A ; weight :9KG

Application field

e-bike

e-scooter

balance car


Golf cart

electric motor

Why you choose us ?

1. We can provide OEM service ,custom your logo both on the product and the packing you want !
2. High quality products ,all of the products must passed strict QC before shipping ,0.01% defective rate !
3. Fastest response rate ,save your time and easy your business !
4. Safe payment methods ,Safe business ,we support T/T,western union ,paypal,trade assurance
5. We provide after-sale service,all of our goods have 1-3 year warranty

		Number	HY00091	
		Version	A0	
	HYLF/48/36-001 Battery pack specification	Date	2019-5-7	
1 Basic characteristics		Product picture		
Product name	Electric car battery	Three yuan soft pack power battery Description: The battery pack is an epoxy resin plate heating plastic sleeve package.		
product code	HYLF/48/36-001			
L x W x H	280mmX160mmx124mm			
Rated voltage	48VSeries structure			
Rated Capacity	36Ah			
Serialization	14S			
Internal resistance	≤100mΩ			
Discharge cutoff voltage	39.2V	Shell color		
Charging protection voltage	58.8V	<input type="checkbox"/> Sub black		
Max.charging voltage	59.5V	<input type="checkbox"/> Bright gray		
Max. charging current	7A	<input type="checkbox"/> +Fruit green + bright gray two-color		
Maximum discharge current	50A	<input type="checkbox"/> White+ black		
Peak current	100±5 2S	<input type="checkbox"/> light blue		
Rated discharge current	30A	<input checked="" type="checkbox"/> Blue thermoplastic film		
		Charging and discharging interface		
		<input type="checkbox"/> Wall terminal		
		<input type="checkbox"/> Anderson		
		<input type="checkbox"/> Navigation plug		
		<input checked="" type="checkbox"/> Positive and negative lines		
		<input type="checkbox"/> Pole		
Charging method	CC/CV	<input type="checkbox"/> Hardware contact		
		<input type="checkbox"/> socket		
weight	9.0Kg	Different rate discharge curves:		
Operating temperature	Charging			0 45
	Discharge			-20 55

60-80%SOC , 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35	
C1 Cycle life	1200 Times	
price	RMB:¥ 00.00	
Delivery period	25 Working day	



Hunan Pinsheng Energy Technology Co., LTD.

15616151876

info@pinshengenergy.com

rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.