



High Capacity 12v Lithium Ion Battery Rechargeable Lithium Ion C Batteries

Basic Information

Place of Origin: Changsha, China

• Brand Name: HYZZ

• Certification: ISO9001, CE, CB, UN38.3

Packaging Details: foam, wooden box / foam, carton, tray

Delivery Time: 22 daysPayment Terms: L/C, T/T

• Supply Ability: 10,000 PCS per month



Product Specification

Name: Rechargeable Li Ion Battery

• Model: 12V 500AH

• L X W X H: 480mm*311.5mm*282.5mm

Working Temperature: -20°C ~ 60°C
 Weight: 56.5Kg
 Shell Color: Sub Black

• Highlight: lithium ion auto battery,

lightweight automotive battery

Product Description

High Capacity 12v Lithium Ion Battery Rechargeable Lithium Ion C Batteries

Model: 12V 500AH

Dimension: 480mm*311.5mm*282.5mm;

Parameter:

working environment:-20 -60 ;Lithium iron phosphate battery 4S;Charge cutoff voltage:14.4V;Discharge cutoff voltage:9.6V; Continuous 240A discharge;50A Charging; Wall terminal with protective cover and LCD display

How to choose a high quality lithium battery:

- 1, A grade battery cell, with full capacity for each battery cell;
- 2, BMS: water proof, anti static, over current protection, over voltage protection, with sealed case;
- 3, IP55 water proof case, plastic or steel case available by customer's requirement. MOQ: 1pieces. In order to guarantee A grade battery cell:
- 1, High grade raw material;
- 2, 12hours & 3 cycles charging/discharging test.

Applications

Smart wearable devices, smart cards, smart electronics intelligent door lock, intelligent lighting, emergency light, industrial cameras. Bluetooth earphone, power bank,MPS, Tablet PC, laptop, GPS

Medical devices, electric children toys, electric shoes, electric blanket.

			Number	HY00078
	UVI E/40/5	:00 001	Version	IAU
		specification	Date	2019-5-7
1 Basic characteristics		Product	picture	
Product name	Industrial lithium battery		Batteries:3.2V100AHLithium iron phosphate battery 3.2V100AH	
product code	HYLF/12/500-001			
LxWxH	480mm*311.5mm*282.5mm			
Rated voltage	12.8VSeries structure			
Rated Capacity	500Ah		_	
Serialization	4S		_	
Internal resistance	≤100mΩ			
Discharge cutoff voltage	9.6V		Shell col	or
Charging protection voltage	14.4V		☑ Sub bla	ack
Max.charging voltage	14.6V		□ Bright	gray
Max. charging current	50A		- +Fruit	green + bright gray two-color
Maximum discharge	240A		□ White	
current	10/1		-□ Blue thermoplastic film	
Peak current	400±2 2S			
Rated discharge current	240A		□ Wall te □ Anders □ Naviga □ Positiv □ Pole	
Charging method	CC/CV			
weight	56.5Kg		_	
	Charging	0 45	1	
Operating temperature	Discharge	-20 55		

60-80%SOC, 2		LCD.Front panel content: through-wall terminal
Storage temperature		with protective cover and LCD display.
60-80% SOC storage,	10.35	
need to recharge	-10 33	
every 2 months		
C1 Cycle life	1500 Times	
Cycle life	1500 Times	
price	RMB:¥ 00.00	
Delivery period	25 Working day	



Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

 $NO.\ 259, Lixiang\ East\ Road,\ Xiangfeng\ Technology\ Industry\ Park,\ Changsha\ City,\ Hunan,\ China.$