



24 Volt 20Ah LifePO4 Lithium Battery Lightweight For E Bike / Power Tools

Basic Information

• Place of Origin: Changsha, China

• Brand Name: HYZZ


• Certification: ISO9001, CE, CB, UN38.3

Model Number: HY00085

• Packaging Details: foam, wooden box / foam, carton, tray

Delivery Time: 22 daysPayment Terms: L/C, T/T

• Supply Ability: 10,000 PCS per month



Product Specification

• Name: LifePO4 Lithium Battery

Model: 24V 20Ah

• L X W X H: 264mmX164mmx64mm

Application: E-bike, Power Tools, New Energy Vehicles

• Charging Protection 28.8V

Voltage:

• Discharge: -20 55

• Highlight: lithium iron phosphate battery,

lifepo4 rechargeable battery

Product Description

24 Volt 20Ah LifePO4 Lithium Battery Lightweight For E Bike / Power Tools

Model: 24V20Ah

Dimension: 264mmX164mmx64mm

Features: iron lithium 81160227/8S; charge cut-off voltage:29.2V; discharge cut-off voltage: 20V; working current:10A; weight:5.6KG

Key advantages

High energy density: more energy with less weight and footprint.

High charge currents (short charge period)

High discharge currents

Ultra-high cycling performance (up to six times the battery life of a conventional battery)

High effciency between charging and discharging

Higher continual power available

Wide operating temperature

Predictable end of life due BMS controller

The loweat possible TCO

Application Lithium battery pack:

E-bike, power tools, new energy vehicles, medical equipment, digital cameras, measuring instruments, robots, etc.

Tips: If you see our products and have questions about the products, please contact our account manager to send your specific needs, such as voltage, capacity, shape, size, working current, etc. We can customize and meet your needs according to your needs. The best lithium battery matched by the equipment, we are very happy to provide you with test samples, and will reply you as soon as possible, thank you!

| | | Number | LIVOOOS |
|-----------------|---|--|---------------------------------|
| | | | |
| HVI F/04/0 | 0.001 | version | A0 |
| | | Date | 2019-5-7 |
| s | | Product | picture |
| Industrial lith | nium battery | | |
| HYLF/24/20 | -001 | | |
| 264mmX164 | 4mmx64mm | Batteries | :Lithium iron phosphate battery |
| 24VSeries s | tructure | | |
| | | | |
| 8S | | | |
| ≤100mΩ | | | |
| 18.4V | | Shell col | or |
| 28.8V | | _ □ Sub bla | ack |
| 29.2V | | □ Bright | gray |
| 10A | | ┨ | |
| 104 | | ─ □ +Fruit | green + bright gray two-color |
| IUA | | □ White+ black | |
| 20±2 2S | | | |
| 5A | | ☑ Blue thermoplastic film Charging and discharging interface ☐ Wall terminal ☐ Anderson ☐ Navigation plug ☑ Positive and negative lines ☐ Pole ☐ Hardware contact | |
| CC/CV | | | |
| 5.6Kg | | _ | |
| Charging | 0 45 | | |
| Discharge | -20 55 | | |
| | Battery packs Industrial litt HYLF/24/20 264mmX164 24VSeries s 20Ah 8S ≤100mΩ 18.4V 29.2V 10A 10A 20±2 2S CC/CV 5.6Kg Charging Discharge | Industrial lithium battery HYLF/24/20-001 264mmX164mmx64mm 24VSeries structure 20Ah 8S ≤100mΩ 18.4V 28.8V 29.2V 10A 10A 20±2 2S CC/CV 5.6Kg Charging 0 45 Discharge -20 55 | Battery pack specification Ses |

| 60-80%SOC , 2 | | |
|---------------------|----------------|--|
| Storage temperature | | |
| 60-80% SOC storage, | -10.35 | |
| need to recharge | 1000 | |
| every 2 months | | |
| C1 Cycle life | 1500 Times | |
| Cycle life | 1500 Times | |
| price | RMB:¥ 00.00 | |
| Delivery period | 25 Working day | |



Hunan Pinsheng Energy Technology Co., LTD.

15616151876

info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.