



CE Approved 18650 Lithium Rechargeable Battery 12 Volt 75Ah For Electric Bike

Our Product Introduction

for more products please visit us on rechargeable-liionbattery.com

Basic Information

- Place of Origin: Changsha, China
- Brand Name: HYZZ
- Certification: ISO9001, CE, CB, UN38.3
- Model Number: HY.NO0008
- Packaging Details: foam, wooden box / foam, carton, tray
- Delivery Time: 22 days
- Payment Terms: L/C, T/T
- Supply Ability: 10,000 PCS per month



Product Specification

- Name: 18650 Lithium Ion Battery
- Model: 12V 75Ah
- L X W X H: 260mmX160mmX158mm
- Application: Illuminate Devices, Miner Lamp, Search Light, Ect...
- Internal Resistance: $\leq 100\text{m}\Omega$
- Weight: 4.8KG
- Highlight: **18650 rechargeable li ion battery ,
18650 lithium rechargeable battery**

Product Description

CE Approved 18650 Lithium Rechargeable Battery 12 Volt 75Ah For Electric Bike

Model: 12V75Ah

Dimension:260mmX160mmx158mm;

Feature:

Conversion time:5ms;Analog sine wave; AC input:AC110V~220V,DC input:DC18V-36V;Car input:12V,DC output:12V,USB: 5V;Weight:4.8KG

Applications

- > Wind-Solar energy system
- > Off-grid energy storage
- > Solar street lights
- > Household energy storage
- > Telecom backup system
- > Mobile base stations
- > Emergency backup energy sources
- > Uninterruptible power system
- > Grid load shifters
- > Electric Golf Car
- > Electric vehicles
- > Electric motorcycles
- > Electric forklifts
- > Electric boats, etc.

		Number	HY.NO0008	
		Version	A0	
	HYLF/12/75-001	Date	2019-5-7	
	Battery pack specification			
1 Basic characteristics			Product picture	
Product name	Portable power supply		Battery: ternary lithium battery	
product code	HYLF/12/75-001			
L x W x H	260mmX160mmx158mm			
Rated voltage	12VSeries structure			
Rated Capacity	75Ah			
Serialization	4S			
Internal resistance	≤100mΩ			
Discharge cutoff voltage	11.2V		Shell color	
Charging protection voltage	16.8V		<input type="checkbox"/> Sub black	
Max.charging voltage	17V		<input type="checkbox"/> Bright gray	
Max. charging current	10A		<input type="checkbox"/> +Fruit green + bright gray two-color	
Maximum discharge current	25A		<input type="checkbox"/> White+ black	
Peak current	50±5 2S			
Rated discharge current	15A		<input type="checkbox"/> Blue thermoplastic film	
			Charging and discharging interface	
			<input type="checkbox"/> Wall terminal	
			<input type="checkbox"/> Anderson	
			<input type="checkbox"/> Navigation plug	
		<input type="checkbox"/> Positive and negative lines		
		<input type="checkbox"/> Pole		
		<input type="checkbox"/> Hardware contact		
Charging method	CC/CV		5ms.,AC110V~220V,DC18V-36V,12V,12V,USB 5V.Features: conversion time 5ms, analog sine wave, AC input AC110V~220V, DC input DC18V-36V, car 12V input, DC output 12V, USB 5V.	
weight	4.8Kg			
Operating temperature	Charging	0 45		
	Discharge	-20 55		
60-80%SOC , 2 Storage temperature 60-80% SOC storage, need to recharge every 2 months	-10 35			
C1 Cycle life	1500 Times			
Cycle life				
price	RMB:¥ 00.00			

Delivery period	25 Working day
-----------------	----------------

FAQ

Q1: How is your battery quality?

Re: our battery have quality guarantee.

Q2: How is battery 's capacity of your company?

Re: All of our batteries are real full capacity .

Q3: How about your company?

Re: 12 years experience to product li-ion battery,focus on battery's quality and research.

Q4: Do you accept OEM/ODM?

Re: We support the OEM/ODM service: Pls don't hesitate to tell us your ideas.

Q5: Which certificates do you have?

Re: We have CE/ROHS.



Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.