



36V 540Wh Ebike Battery Electric Bicycle Lithium ion Battery Pack 48V 500W 1000W E-bike Battery

Basic Information

• Place of Origin: China

• Brand Name: Pinsheng Energy

• Certification: CE, MSDS, UN38.8 , ISO9001

Model Number: PE3615Minimum Order Quantity: 10

• Price: USD125-145/pc

Packaging Details: carton box, UN box, wooden box

• Delivery Time: 10-20days

Payment Terms:
 L/C, D/A, D/P, T/T, Western Union,

MoneyGram

Supply Ability: 10000pcs/month



Product Specification

Product Name: 36V 15Ah Ebike Battery Pack

Material: ABS Plastic
Size: 378*78mm
Weight: 3.9kgs
Voltage: 36V
Capacity: 15Ah
Charging Cut Off Voltage: 30V
Discharging: 42V

• Highlight: 48V 500W Ebike Battery, 1000W Ebike Battery,

36V 540Wh Ebike Battery



More Images



Product Description

36V 540Wh Ebike Battery Electric Bicycle Lithium ion Battery Pack 48V 500W 1000W E-bike Battery

Model: PE4810-2

Parameters:

1. Product Name: 36V 15Ah Ebike Battery Pack

2. Dimension: 378(L)*78(W)mm

3. Weight: 3.9Kgs

4. Material: Aluminum+ Steel 5. Color: Silver / Customized 6. Working Voltage: 36V

7. Capacity: 15Ah8. Charging Cut Off Voltage: 30V9. Discharging Limit Voltage: 42V10. Battery Cell: NCM

11. Working Temperature: -20°C ~ 60 12. Charging Temperature: 0°C ~ 55

Application

Widely use for E-bike, Electric Bicycle, E-scooter, Electric Scooter

Item	Detail
Product Name	36V E-bike Battery
Series - Parallel Mode	10S6P
Cycle Life	4000 Times 100% DOD
Dimension	378 * Dia 78 mm
Weight	3.9Kgs
Battery Box Material	Aluminum Alloy
Color	Customized
Working Voltage	36 Volts
Capacity	15 Ah
Charging Cut Off Voltage	30 Volts
Discharging Limit Voltage	42 Volts
Battery Cell	NCM LFP Cylindrical
Working Temperature	-20°C ~ 60°
Charging Temperature	0 ~ 55
Working Humidity	85 %
Internal Resistance	2mΩ
Self Discharging Rate	3% P
OEM / ODM	Support
Charging / Discharging Interface	Customized

Battery Cell







Item	Detail
Battery Type	NMC
Capacity	Ah, 8Wh @C2, 25 °C
Nominal Voltage	3.6V DC
Cycle Life @ 100% DOD	>2500 Cycles(100% @C2, 25 °C)
Cycle Life @ 80% DOD	>3500 Cycles(80% @C2, 25 °C)
Cycle Life @ 70% DOD	>4500 Cycles(70% @C2, 25°C)
Dimensions	Dia18mm(L)x30mm(W)x185mm(T)
Weight	41g
Charging Cut-off Voltage	3V
Discharging Limit Voltage	4.2V
Charging Under/Over Temp Protection	0 °C /55 °C
Charging under/over Temp Protection	-20 °C /60 °C

Notes

- 1. Large-scale electric vehicles: electric bus, electric car, E-Tour Car
- 2. Light electric car: e-bike, e-scooter, e-motorcycle, electric golf cart, e-wheelchair
- 3. E-tool: electric drill, electric saw, lawn mower and so on
- 4. Remote control cars, electric boat, aircraft, toys
- 5. Solar and wind power generation energy storage devices, solar systems, Telecom base Station
- 6. Small medical equipment and portable equipment
- 7. RV, Camping car and yacht
- 8. Solar enegery lights, bicycle lights, LED lights, bright flashlight, solar street lights













Hunan Pinsheng Energy Technology Co., LTD.



15616151876



info@pinshengenergy.com



rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.