



pinsheng 3.2v 100ah lifepo4 battery cell/lifepo4 3.2v 100ah polymer prismatic pouch battery cell

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1
- Delivery Time:
- Payment Terms: T
- Supply Ability:
- pe2246 ity: 1PCS 15-25 work days T/T, Western Union, MoneyGram 30000+set+per month

hunan,china

ce

pinsheng Energy



Product Specification

- Product Name:
- Model Number:
- Capacity:
- Nominal Voltage:
- Storage Type:
- Sealed Type:
- Application:
- Cycle Life:
- Highlight:

L	.ifePO	4 Lithiu	m Battery


Pe2246

280ah

- 3.2V
- Standard Sealed
- oculou
- Solar Energy Storage Systems
- 3500times
 - 3.2v 100ah lifepo4 battery cell, lifepo4 3.2v 100ah battery cell

PINSHENG





Company Display



Hunan Pinsheng Energy Technology Co.,LTD





CERTIFICATE







Key Features of Pinsheng Lithium Battery

- 1. Long life, large capacity and good shock resistance
- 2. Low self discharge and good discharge performance at low temperature
- 3.Strong charing acceptace and quick- charging capability
- 4. Storage over- discharge resistance and charge retention
- 5.Maintenance-free and no acid or water for mantence in usage
- 6. Excellent large current discharge performance, and have obvious
- advantages in startup and climing
- 7. High temperature performance
- 8. Environmental friendly
- 9. Lighter weight smaller size

10.Good service

Specifications:

Items	Specifications

Nominal Voltage	3.2V
Nominal Capacity	280Ah
Standard Charge Current	0.2C-0.5C
Max. Charge Current	1C
Continuous Discharge Current	1C
Peak Discharge Current	2C
Charge Cut-off Voltage	3.9V
Discharge Cut-off Voltage	2V
Inner Resistance	\leq 0.3m Ω (At 0.2C rate, 2.0V cut-off)
Weight	5.5kg
Dimension	Length: 205mm Width: 175mm Thickness: 72mm
Operating Temperature	Charging: 0°C ~ 45°C Discharging: -20°C ~ 55°C


Storage Temperature	optimal store temperature of 23 \pm 5°C for long term storage
Life Cycle	≥3500 times (100% DOD till 80% of initial capacity at 0.2C rate, IEC Standard)

Gravimetric Energy Desity(Wh/kg)	110-190	20-50	
Volumetric Energy Density(Wh/Kg)	170-310	60-90	
Cycle Durability	>3000 cycles	300-500 cycles	
Self discharge Rate	<2%	<4%	
Discharge Rate	10C	1C	
Installation	Smallsize and light weight ,about40% of the weight of a comparable elead acid battery	Big and heavy, difficult to install	
Maintenance	No need for regular maintenance	Regular manintenance staff required	
Enviromental Protection	Freee of hearby metals, safe and pollition free recycling utilization rate is high	Containing hearvily pollutiong and toxic substances ,such as lead,arsenic, mercury	
Superior safety	lihtium Iron phosphate chemistry reduces the ris of explosion of combustion		















PAYMENT&LOGISTICS



Contact Us



Sofia Tse Sales Manager

Liver Die

Hunan Pinsheng Energy Technology Co.,LTD



2/F,Building 4,Xiangfeng High-Tech Industrial Park,Changsha County, Changsha City, Hunan Province M.P.:+86-15675831763/13307465388 P.C: 410100 E-Mail: sofiatse210816@gmail.com





info@pinshengenergy.com

@ rechargeable-liionbattery.com

NO. 259, Lixiang East Road, Xiangfeng Technology Industry Park, Changsha City, Hunan, China.